

## Balance 670 Tile

**Designer:** Woven Image

**Application(s):** Walls, Ceilings

### Composition & Pattern

**Composition** 100% PET (60% post-consumer recycled)

**Colours Available** 14

### Kit & Box Content

**Quantity in Box** 12

### Dimensions & Weight

**Dimensions** Length: 670mm (+/-2 mm), Width: 335mm (+/- 2mm), Thickness: 24mm (+/- 7%)

**Unit of Sale** Box

**Unit of Sale Net Weight (kg)** 9

## Performance

<b>Fire Test Result</b>	ISO 9705: Group 1, BS EN 13501.1: Classification B - s1, d0, BS EN 45545-2 + A1 Annex C: CIT: 0.00, ASTM E84 Unadhered: Class 1 or A
<b>Acoustic Performance Standard Test Method</b>	AS ISO 354: 2006 (R2016)
<b>Noise Reduction Coefficient (NRC) Result</b>	Direct fix: 0.65
<b>Sound Absorption Average (SAA) Result</b>	Direct fix: 0.63
<b>Weighted Sound Absorption Coefficient (<math>\alpha_w</math>) Result</b>	Direct fix: 0.45 (MH)
<b>Sound Absorption Class</b>	D (Direct fix)
<b>Additional Acoustic Information</b>	Sound Absorption Class result is based on EchoPanel® 24mm. MH = Mid to High Frequency
<b>Colour Fastness to Light Standard Test Method</b>	ISO 105 B02
<b>Colour Fastness Light Rating</b>	6 - 7

## Sustainability

**VOC Emissions Results** EchoPanel 24mm achieves ASTM D5116: TVOC Emissions Rate:  $<0.02\text{mg}/\text{m}^2/\text{hr}$  (7 days), and CDPH Standard Method v1.2: TVOC Emissions Rate:  $<0.054\text{mg}/\text{m}^3$ ; Formaldehyde Emissions Rate:  $<2\mu\text{g}/\text{m}^3$

**Sustainability Performance**



**Sustainability Performance Details** EchoPanel achieves GreenTag Certification GreenRate: Level A &

Health Rate Platinum, Red List Free, and has an International Living Future Institute Declare Label.

## Instructions

**Additional Information** See Woven Image EchoPanel Care & Cleaning Guide.  
See Woven Image Tiles Installation Guide.

Exact colour matching cannot be guaranteed between batches.  
Fibre mix and web variation are natural characteristics of this product.

